

## Solar Control Film

Lower Mirror - Sputtered Grey 20 - External

**Code:** SO-20SG-eSR



### Performance Data

#### Total Solar Energy

Transmitted	23%
-------------	-----

Reflected	28%
-----------	-----

Absorbed	49%
----------	-----

#### Visible Light

Transmitted	22%
-------------	-----

Reflected	30%
-----------	-----

Ultra-Violet Rejected	<99%
-----------------------	------

Glare Reduction	75%
-----------------	-----

Shading Coefficient	0.40
---------------------	------

Total Solar Energy Rejected	68%
-----------------------------	-----

Product Warranty	7/4 years
------------------	-----------

#### Specification:

The solar control window film is to be **SO-20SG-eSR**, as supplied by Partition Graphics ([www.partitiongraphics.com](http://www.partitiongraphics.com)). The film is to be installed to the **exterior** surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.

(For exterior grade film also insert, **Exterior grade films must be correctly edge sealed**).

#### Notes:

Test results are produced from film applied to clear glass. Performance data is subject to change without prior notice. Accurate selection of window film requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct or consequential loss howsoever arising.